ARCHI

3D TILE

CEILING

Direct

ARCHI a curved acoustic ceiling tile defined by its sculpted, arched profile. The gentle curvature introduces soft movement across the ceiling, enhancing light flow and adding a sense of depth and elevation. Available in curated finishes or custom shades.



SYSTEMS

T24 (EU only)

SIZES


595x1100mm (23.42x43.31")

THICKNESS

12mm (0.47")

MOQ

6 Units in a single color



HOW TO PLACE AN ORDER

ARCHI offers versatile possibilities for shaping your space. As you plan your layout, take a moment to reflect on a few guiding questions to help refine your design.

Please note that the tiles cannot be cut, so the ceiling must be planned using full tiles only. Accurate planning will ensure a seamless and visually pleasing result.

minimum order quantities :
6 Units in a single color



Choose your desired color from our color palette – printing option available

PAGE 4




Ensure the wall dimensions meet the required specifications

PAGE 5

GEOMETRIC

MODELS



COLORS

echoshape panels are crafted from 12mm PET felt, serving as the core material in our acoustic solutions. Available in a curated range of colors, these panels are designed to enhance both the visual and acoustic qualities of any space.

Choose from subtle neutrals for a seamless look, or introduce bold tones to create striking contrasts. Due to the nature of the PET felt manufacturing process, a soft heathered texture may appear, blending multiple shades within each panel. As a result, slight color variations between units are natural and reflect the sustainable, recycled origin of the material.

Please note: colors may appear differently on screens or in print. For accurate color matching, we recommend requesting a physical sample.




PRINTED PATTERNS

echoshape panels are crafted from 12mm PET felt, serving as the core material in our acoustic solutions. Available in a curated range of colors, these panels are designed to enhance both the visual and acoustic qualities of any space.

Choose from subtle neutrals for a seamless look, or introduce bold tones to create striking contrasts. Due to the nature of the PET felt manufacturing process, a soft heathered texture may appear, blending multiple shades within each panel. As a result, slight color variations between units are natural and reflect the sustainable, recycled origin of the material.

Please note: colors may appear differently on screens or in print. For accurate color matching, we recommend requesting a physical sample.






























SPECIFICATIONS


MANUFACTURED FROM	Panels
COMPOSITION	100% Polyester (PET)
SUSTAINABILITY	70% Recycled plastic bottles
APPLICATION	Ceiling tiles
FIRE RATING	EN13501-1 | B S-1 d0 ASTM E-84 – Class A
SIZE	595x1100mm (23.42x43.31")
THICKNESS	10mm TOLERANCE ±7%
INSTALLATION	Mounted on structural ceiling: T24 (EU only)
ACOUSTIC RESULTS	Measurement results Echoshape mounted at an airgap of 0 mm α_w 0.25 / NRC 0.30 Measurement results Echoshape mounted at an airgap of 50 mm α_w 0.55 / NRC 0.65 Measurement results Echoshape mounted at an airgap of 200 mm α_w 0.85 / NRC 0.80
ACOUSTIC CERTIFICATE	ISO 354:2003 EN ISO 22654: 1997 ASTM C423-17
VOC	According to EN ISO 16000-9 Standard: A+
CARE	Indoor use only. Clean with a damp cloth or vacuum. For spills, blot, immediately use water with a soft cloth, and if needed, mild detergent. Dry while still wet. For stubborn stains, try water first, then mild detergent.

INSTALLATION GUIDE


THESE ARE YOUR PARTS




L Profile (Optional)




T Main Profile




T Side Profile



Adjustble Hanger




Tiles




1

A connecting spline runs through two Archi tiles and hangs on the side profile of the T ceiling grid.



2

Install the Archi tiles on either on the T ceiling grid. or glue it directly to the ceiling



3

Repeat the process for the entire ceiling